

# EPIC Series



## WOOFERS

## DRIVERS

Technical Specifications	EPIC 8	EPIC 10	EPIC 12	EPIC 15	EPIC 18	EPIC 1.75	EPIC 3	EPIC 4
Power (AES)	200	250	450	700	800	60	110	160
Power (Peak)	400	500	900	1400	1600	120	220	320
Frequency Response (Hz)	95-6000	55-3500	42-3000	37-1500	30-1200	1000-18000	600-18000	600-18000
SPL (dB)	95	95	96	97	97	107	108	108
Impedance (Ohm)	8	8	8	8	8	8	8	8
Voice coil dimensions (inch)	2	2,5	3	4	4	1,75	3	4
Magnet weight (Oz)	56,3	54	76	121,5	121,5	30	100	100
Die Cast Frame	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum	Aluminum
Overall Dimension (mm)	225	262	316	374	440	120	170	220
Fits Enclosure Hole Size (mm)	190	230	282	354	422	—	—	—
Mounting Depth (mm)	102	124	136	168	197	62	64	130
Weight (kg)	4,2	6	7,1	11	13	2,1	4,5	10,2
Throat	—	—	—	—	—	1" Throat Bolt 2 x M6 Holes 180 on 76mm Ø	2" Throat Bolt 4 x M6 Holes 180 on 102mm Ø	2" Throat Bolt 4 x M6 Holes 180 on 102mm Ø



# PUNCH Series

## WOOFERS

Technical Specifications	PUNCH 815	PUNCH 1020	PUNCH 1220	PUNCH 1225	PUNCH 153	PUNCH 154	PUNCH 184
Power (AES)	160	260	300	350	450	500	600
Power (Peak)	320	520	600	700	900	1000	1200
Frequency Response (Hz)	70-3500	60-3500	60-3500	50-3500	43-1500	40-1500	30-1500
SPL (dB)	94	95	95	96	96	96	97
Impedance (Ohm)	8	8	8	8	8	8	8
Voice coil dimensions (inch)	1,5	2	2	2,36	3	4	4
Magnet weight (Oz)	39	39	44	46	60	100	100
Die Cast Frame	Steel	Steel	Steel	Steel	Steel	Steel	Steel
Overall Dimension (mm)	203	259	312	312	387	387	460
Fits Enclosure Hole Size (mm)	182	232	277	277	352	352	424
Mounting Depth (mm)	92	115	126	126	158	158	195
Weight (kg)	3,2	3,5	5,5	6,5	7	8,5	10,5